

ダイヤル径 DIAL SIZE	(□)	A	B	C	D
▷ 100	4	12.5	47	111	100
▷ 125	5	15	48	129	119
▷ 150	6	15	49	161	149


取合フランジ FLANGE CONNECTION

JIS10K	M	t	R	Q	0
▷ 15A	15	12	51	70	95
▷ 20A	15	14	56	75	100
▷ 25A	19	14	67	90	125

JIS20K	M	t	R	Q	0
▷ 15A	15	14	51	70	95
▷ 20A	15	16	56	75	100
▷ 25A	19	16	67	90	125

記号 SYM	訂正 REVISION	作成 REV. BY	日付 DATE

注：指定なき寸法許容差は±1  
ALLOWANCE ±1 (EXCEPT APPOINTED SIZE)



9	ダイヤフラム DIAPHRAGM	仕様書参照 REFER TO SPEC. SHEET
8	圧力取出口 PRESS. PORT	仕様書参照 REFER TO SPEC. SHEET
7	ブローアウトキャップ BLOWOUT	ネオプレン NEOPRENE
6	株 SOCKET	316LSS
5	指針(零調可) POINTER	SUS304
4	目盛板 DIAL PLATE	アルミ板 ALUMINUM PLATE
3	透明板 GLASS DISK	安全ガラス SAFETY GLASS
2	表面カバー COVER	304SS
1	ケース CASE	304SS
No.	名称 NAME	材質 MATERIAL

NESS NESSTECH INC.

タイトル  
TITLE 隔膜式圧力計  
SEALD DIAPHRAGM GAUGE  
WITH I SECTION FLANGE (JIS)

尺度 SCALE	作成 DR. BY	承認 APPD.
f.		

型式 MODEL NO.	PB-DUNS-JIS	
図番 DRAWING NO.		